

t3

Advanced hot tap technology for superior, sustainable hot & chilled drinks.



Overview

- Intelligent hot tap technology.
- Premium aesthetic.
- Powerful and energy-efficient.
- Intelligent energy-efficiency
- Hygiene assurance in every pour.
-
- Bluetooth® touchless water dispensing

Specifications

- Chilled temperature - 2°C
- Hot temperature - 92°C
- ProCore+ flow rate - 80L/h
- ProCore flow rate - 50L/h
- Hot flow rate - 16L/h

Accessories

- [500ml water bottles](#)
- [Printed paper cups 463428](#)
- [Install kit with 3M filter 461202](#)
- [Refill station cabinet 601604](#)

Tap: W160xD324xH338mm

T3 ProCore ProCore: W320xD471xH400mm - Includes the Simple-fit Ventilation Base

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled, Ambient & Hot	Dry Chill®	1670W	743160	743170	743180	743190
Chilled, Sparkling, Ambient & Hot	Dry Chill®	1670W	743240	743250	743260	743270

Tap: W160xD324xH338mm

T3 ProCore+ ProCore: W320xD471xH400mm - Includes the Simple-fit Ventilation Base

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled, Ambient & Hot	Dry Chill®	1710W	743480	743490	743500	743510
Chilled, Sparkling, Ambient & Hot	Dry Chill®	1710W	743560	743570	743580	743590

borg &
overström

Find out more:

<https://www.borgandoverstrom.com/en/p/tap-systems/t3/>