

# t3

Advanced hot tap technology for superior, sustainable hot & chilled drinks.



## Overview

- Intelligent hot tap technology.
- Premium aesthetic.
- Powerful and energy-efficient.
- Intelligent energy-efficiency
- Hygiene assurance in every pour.
- 

## Specifications

- Chilled temperature - 2°C
- Hot temperature - 96°C
- ProCore+ flow rate - 80L/h
- ProCore flow rate - 50L/h
- Hot flow rate - 16L/h

## Accessories

- [500ml water bottles](#)
- [Printed paper cups 463428](#)
- [Install kit with 3M filter 461202](#)
- [Refill station cabinet 601604](#)

Tap: W160xD324xH338mm

**T3 ProCore** ProCore: W320xD471xH400mm - Includes the Simple-fit Ventilation Base

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled, Ambient & Hot	Dry Chill®	1670W	<a href="#">743160</a>	<a href="#">743170</a>	<a href="#">743180</a>	<a href="#">743190</a>
Chilled, Sparkling, Ambient & Hot	Dry Chill®	1670W	<a href="#">743240</a>	<a href="#">743250</a>	<a href="#">743260</a>	<a href="#">743270</a>

Tap: W160xD324xH338mm

**T3 ProCore+** ProCore: W320xD471xH400mm - Includes the Simple-fit Ventilation Base

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled, Ambient & Hot	Dry Chill®	1710W	<a href="#">743480</a>	<a href="#">743490</a>	<a href="#">743500</a>	<a href="#">743510</a>
Chilled, Sparkling, Ambient & Hot	Dry Chill®	1710W	<a href="#">743560</a>	<a href="#">743570</a>	<a href="#">743580</a>	<a href="#">743590</a>

borg &  
overström

Find out more:

<https://www.borgandoverstrom.com/en/p/tap-systems/t3/>